XC2141 Series

ICs for use with Crystal Oscillators

■GENERAL DESCRIPTION

The XC2141 series are a group of high frequency, CMOS low power crystal oscillators with on-chip divider circuitry that operate from a supply voltage of 3.5V.

■APPLICATIONS

- ●Crystal oscillator modules
- ●Communication equipment
- ●Microcomputers
- ●Clock units in motor control
- ●System clocks on boards
- ●Timers
- ●Palmtops

■FEATURES

Oscillation Frequency : 20MHz ~ 58MHz
Divider Ratio : f0/1
Output : 3-State
Operating Voltage Range : 3.5V ±10%
Small Quiescent Current : 10mA (FOSC=53MHz)
Stand-By Funct
CMOS : Low Power Consumption
Ultra Small Package : SOT-26 (150mW)
Environmentally Friendly : EU RoHS Compliant, Pb Free

■PIN CONFIGURATION



SOT-26
(TOP VIEW)

■PIN ASSIGNMENT

PIN NUMBER	PIN NAME	FUNCTION
1	/INH	Control *
2	XT	Oscillator Connection (Input)
3	VSS	GND
4	Q0	Output
5	VDD	Power Supply
6	/XT	Oscillator Connection (Output)

* Control pin has pull-up resistor built-in.

■INH, Q0 PIN FUNCTION

/INH	Q0
"H"	Output
open	Output
"L"	High Impedance (oscillation stopped)

"H" = High level
"L" = Low level

■PRODUCT CLASSIFICATION

●Ordering Information

XC21①②③④⑤⑥⑦⑧-⑨(*1)

DESIGNATOR	DESCRIPTION	SYMBOL	DESCRIPTION
①	Supply Voltage	4	: 3.5V
②	Product Series	1	: Large output capability, fundamental & overtone
③	Duty Level	C	: CMOS (VDD/2)
④	Fixed Number	2	: Fixed
⑤	Divider Ratio	1	: f0/1
⑥	Fundamental / Overtone Rf, Cg, Dc	A	: No Rf, Cg, Cd = 2pF
⑦⑧-⑨	Packages Taping Type (*2)	MR-G	: SOT-26

(*1) The “-G” suffix indicates that the products are Halogen and Antimony free as well as being fully RoHS compliant.
(*2) The device orientation is fixed in its embossed tape pocket. For reverse orientation, please contact your local Torex sales office or representative. (Standard orientation: ⑦R-⑨, Reverse orientation: ⑦L-⑨)

■STANDARD PARTS

PART NUMBER	DUTY LEVEL	DIVIDER	Rf	Cg & Cd
XC2141C21A	CMOS (VDD/2)	f0/1	External	External

Cg & Cd: Add a 2pF capacitor between VDD & XT and/or VDD & XT/. As the parasitic capacitance, Cg and Cd's capacitance is equivalent of 2pF.

■BLOCK DIAGRAM



■ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	CONDITIONS	UNITS
Supply Voltage	V_{DD}	V_{SS} - 0.3 ~ V_{SS} + 7.0	V
Input Voltage	V_{IN}	V_{SS} - 0.3 ~ V_{DD} + 0.3	V
Power Dissipation	Pd	150	mW
Operating Temperature Range	Topr	-30 ~ +75	℃
Storage Temperature Range	Tstg	-55 ~ +125	℃

■ELECTRICAL CHARACTERISTICS

XC2141C21AMR (Overtone) f0/1

V_{DD}=3.5V, F_{OSC}=53MHz, Rf=7.5kΩ, No Load, Ta = 25℃

PARAMETER	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Operating Supply Voltage	V_{DD}		3.15	3.50	3.85	V
Oscillation Start-Up Time	T_{ST}		–	5.00	–	ms
Input Voltage 'High'	V_{IH}		2.4	–	–	V
Input Voltage 'Low'	V_{IL}		–	–	0.4	V
Output Current 'High'	I_{OH}	V_{OH} = 3.15V	–	- 8	–	mA
Output Current 'Low'	I_{OL}	V_{OL} = 0.35V	–	12	–	mA
Supply Current 1	I_{DD1}	/ I_{NH} = OPEN, Q0 = OPEN	–	–	10	mA
Supply Current 2	I_{DD2}	/ I_{NH} = "L"	–	–	520	μA
Input Pull-Up Resistance	R_{UP}	/ I_{NH} = 3.15V	50	–	200	kΩ
Output Disable Leak Current	I_{OZ}	/ I_{NH} = "L"	–	–	10	μA

■SWITCHING CHARACTERISTICS

CMOS Duty, V_{DD}=3.5V, Load = 15pF, Ta = 25℃

PARAMETER	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Output Rise Time	T_{TLH}	0.1V_{DD} → 0.9V_{DD}	-	-	9	ns
Output Fall Time	T_{THL}	0.9V_{DD} → 0.1V_{DD}	-	-	8	ns
Duty Cycle 1	DUTY 1	at V_{DD}/2, f0/1 Output	40	-	60	%





■PACKAGING INFORMATION

●SOT-26



■MARKING RULE



SOT-26
(TOP VIEW)

①Represents divider ratio

MARK	RATIO
E	f0/1

②Represents duty level

MARK	DUTY LEVEL
2	CMOS (V_{DD}/2)

③Represents 'A' which equals 'No Rf, Cg, Cd = 2pF'

④Represents assembly lot number
(based on internal standards)

1. The products and product specifications contained herein are subject to change without notice to improve performance characteristics. Consult us, or our representatives before use, to confirm that the information in this datasheet is up to date.
2. We assume no responsibility for any infringement of patents, patent rights, or other rights arising from the use of any information and circuitry in this datasheet.
3. Please ensure suitable shipping controls (including fail-safe designs and aging protection) are in force for equipment employing products listed in this datasheet.
4. The products in this datasheet are not developed, designed, or approved for use with such equipment whose failure of malfunction can be reasonably expected to directly endanger the life of, or cause significant injury to, the user.
   (e.g. Atomic energy; aerospace; transport; combustion and associated safety equipment thereof.)
5. Please use the products listed in this datasheet within the specified ranges.
   Should you wish to use the products under conditions exceeding the specifications, please consult us or our representatives.
6. We assume no responsibility for damage or loss due to abnormal use.
7. All rights reserved. No part of this datasheet may be copied or reproduced without the prior permission of TOREX SEMICONDUCTOR LTD.

TOREX SEMICONDUCTOR LTD.